

# Service Doors

Rolling Doors


**C.H.I.**  
a NUCOR company



6266 shown in stainless steel #4 finish and outside mounted.

## VERSATILE AND TOUGH.

C.H.I. rolling service doors are engineered and designed for the toughest of environments. Rolling doors are built to provide a high degree of confidence for specifiers and end users for a wide variety of unique applications. Choose from slat profiles, gauges, mounting options, material, and color options to customize the door to fit your building's needs.



### ■ BEST MARKET USES

Industrial • Grain Elevators • Exterior Mounted Doors •  
Parking • High Security • Non-Insulated Storage • Large Openings

## MODEL SELECTION CHART

	Model	Slat Profile	Slat Material	Gauge	Insulation / R-Value <sup>3</sup>	Max. Size <sup>2</sup>	Colors <sup>1</sup> / Finishes <sup>1</sup>	
Curved Slat	<b>6180</b>	C2.6	Steel	18 Gauge	Non-Insulated	30'0" x 28'0"	Gray, White, PC	
	<b>6200</b>			20 Gauge		28'4" x 28'0"	Gray, White, Galvanized, PC	
	<b>6220</b>			22 Gauge		20'4" x 20'4"	Gray, White, Tan, Brown, Galvanized, PC	
Flat Slat Non-Insulated	<b>6181</b>	F2.5	Steel	18 Gauge	Non-Insulated	30'0" x 28'0"	Gray, White, PC	
	<b>6201</b>			20 Gauge		28'4" x 28'0"	Gray, White, Galvanized, PC	
	<b>6221</b>			22 Gauge		20'4" x 20'4"	Gray, White, Tan, Brown, Galvanized, PC	
	<b>6241</b>			24 Gauge		12'0" x 14'4"		
	<b>6244</b>	F2.7	Aluminum	16 Gauge [.050]		14'4" x 18'4"	Clear Anodized	
	<b>6266</b>		Stainless Steel	22 Gauge		18'4" x 20'4"	#4 Finish	
Flat Slat Insulated	<b>6182</b>	F2.5	Steel	<b>Front:</b> 18 Gauge <b>Back:</b> 24 Gauge	Polystyrene / R-4.7	30'0" x 24'0"	<b>Front:</b> Gray, White, PC <b>Back:</b> Gray, White, Tan, Brown, Galvanized, PC	
	<b>6202</b>	F2.7		<b>Front:</b> 20 Gauge <b>Back:</b> 24 Gauge	Polyurethane / R-7.2	30'0" x 24'0"	<b>Front:</b> Gray, White, Galvanized, PC <b>Back:</b> Gray, White, Tan, Brown, Galvanized, PC	
	<b>6222</b>			<b>Front:</b> 22 Gauge <b>Back:</b> 24 Gauge		24'4" x 20'4"	<b>Front/Back:</b> Gray, White, Tan, Brown, Galvanized, PC	
	<b>6242</b>			<b>Front:</b> 24 Gauge <b>Back:</b> 24 Gauge		24'4" x 16'4"		

<sup>1</sup> Refer to your local Dealer for exact color or finish match. <sup>2</sup> Sizes displayed as width x height. Consult factory for larger sizes. <sup>3</sup> R-values have been calculated in accordance with ASTM C518 standards.

PC = doors available in 188 powder coated options.

### CURTAIN PROFILES



Curved [C2.6]



Flat [F2.5]



Flat [F2.5] - Polystyrene



Flat [F2.5] - Perforated



Flat [F2.5] - Fenestrated




Flat [F2.7]




Flat [F2.7] - Polyurethane


### MOUNTING OPTIONS Interior/Exterior



Steel



Wood



Masonry

### OPERATION

LiftMaster® commercial door operators will keep your rolling door in operation safely and efficiently so your business can keep running smoothly. Rolling Doors can be specified for manual, chain, or motor operation based on size requirements.

