







ng Panel lows p25 & 27

vs p26 & 27



# **Recessed Long Panel Model 2063**

(Not available in 24" sections)
Carriage Windows p25 & 27 Model 2073 ◊

(Not available in 24" sections) Ranch Windows p26 & 27



# **Raised Ranch Panel**

**Model 2070** Ranch Windows p26 & 27 Model 2067◊

Carriage Windows p25 & 27

Model 2087◊ Standard Windows p24 & 27



# Raised Standard Panel Model 2080

Standard Windows p24 & 27

**Model 2068**◊

Carriage Windows p25 & 27 Model 2078 Ranch Windows p26 & 27



# **Raised Sculptured Panel Model 2090**

Standard Windows p24 & 27

**Model 2069**◊

Carriage Windows p25 & 27 Model 2079◊

Ranch Windows p26 & 27 Insulated Stee

# **Color Options**

Wood Grain











Uni-Directional Uni-Directional American Walnut English Oak

Uni-Directional

Uni-Directional Mahogany









Graywood

**Uni-Directional** 

Cedar **Plank** 

American Walnut Plank

English Oak **Plank** 

Plank and Bi-Directionals color options feature a light stucco embossment. Uni-Directionals color options feature a wood grain embossment \*Bi-Directional colors are available on 60, 61, 63, and 64 models with or without windows. They are only available on 71, 72, 73, 74, 81 and 82 models without windows.

### Solid



\*\*These colors include a cool chemistry paint finish but is not recommended for projects with extreme exposures to heat and sunlight.

> Due to the printing process, colors may vary. For accurate color samples, contact a Haas Door dealer for a color selector.

# **FEATURES**

- 2" Thick with Full Thermal Break
- 0.094 Tested U-Factor with an Air Infiltration Joint Seal that meets **IECC** Requirements
- Environmentally Compliant Polyurethane Insulation
- 26-Gauge Galvanized Steel
- Available with Wind Load & Impact Options
- Decorative Glass Options (pg 27)
- SelectView Options (pg 22-23)
- 37 Window Options (pg 24-27)
- Industry Leading Warranty (pg 30)
- Lifetime Rust-Through & Delamination
  - Finish Warranty (pg 30)
  - 6 Year Hardware
  - 3 Year Spring
  - 1 Year All Other Components



2000 series doors include Air Infiltration Seals, which exceed the ASHRAE 90.1 Standard when installed with standard bottom seal and commonly available rigid/flexible vinyl door stop.

A Full Thermal Break is used in the tongue-andgroove construction. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.



# Panel Options



## Flush Panel Model 2010

All colors except Bi-Directional wood grains Carriage Windows p25 & 27 Ranch Windows p26 & 27 TL Windows p26 Standard Windows p24 & 27 SlimLine Windows p26



# V-Groove Panel **Model 2012**

All colors except Bi-Directional wood grain & Plank options Carriage Windows p25 & 27 TL Windows p26 SlimLine Windows p26



# **Ribbed Short Panel Model 2060**

Carriage Windows p25 & 27

**Model 2072** 

Ranch Windows p26 & 27 Model 2082◊ Standard Windows p24 & 27



#### **Recessed Short Panel Model 2061**

Carriage Windows p25 & 27 **Model 2071** 

Ranch Windows p26 & 27

Model 2081◊ Standard Windows p24 & 27



Ribbed Lo **Model 2064** Carriage Wind **Model 2074** Ranch Window